



Line Marking and Floor Painting Systems

Lines, Walkways, Flood Floors, Stencils, 5S Demarcation



Total Rapidshield™

The Total Rapidshield™ linemarking system uses specialist polyurethane coatings which are cured instantly using high powered Ultra-Violet light. The coatings are applied to a pre-prepared floor, in 4 layers: 1 Primer + 2 Colour Coats + 1 Top Coat. Each layer is baked onto the floor, leaving a hardened surface, which offers outstanding durability and visible markings that are easy to maintain. These lines will last up to 5 years under normal site conditions.

- Expected 5 year life
- Reduced Downtime - Instant Cure
- Easy to keep clean
- Full installation by inotec technical teams

Duraline Rapidshield™

Our Duraline Rapid system uses a conventional linemarking paint which dries in 4 hours. Although not as durable as the Duraline Epoxy paint on it's own – the Duraline Rapid System gains it's Durability from a Rapidshield™ clear UV coating. This is applied on top of the colour coat and cured instantly using high powered Ultra-Violet light. This forms an extremely hard durable surface giving a an expected lifespan of 3-4 years under heavy traffic conditions. This system also has the added advantage of a quick hand back – areas can be finished in an 8 hour shift and are ready for use.

- Expected 3-4 year life
- Reduced Downtime
- Easy to keep clean
- Full installation by inotec technical teams

Duraline : 2 Pack Epoxy Paint

Our Duraline Linemarking is a 2 Pack Epoxy Paint formulation applied using an airless spray machine. We can pre-prepare the surface with either shot blast or diamond polishing, which gives a perfect 'key' for the paint and makes the bond to the floor extremely strong. The paint system is then applied in 2 coats. This system can be used for both internal and external yard markings. Full curing for heavy traffic will take 24 hours at 10°C. This process makes Duraline much more durable than conventional linemarking paints offering a minimum of 2 years use even in heavy traffic conditions - minimising costly remarking and touch-up regimes.

- Expected 2-3 year life span
- Ideal for Marshalling Lanes and Walkways
- Full installation by inotec technical teams

***Instant UV cure
 reduces downtime***

***Easy to Clean
 more visible lines
 for longer***

***Suitable for
 Chilled and Freezer***

***Free from VOC's
 or Solvents***

Cad Design Service

***Stencils and Safety
 Markings***

***Flood Floors
 Walkways and Zebras***

***Cost effective
 durable markings***

***inotec Safe Contractor
 Installation***